

TECHNICAL DATA SHEET

30 - 03 - 2007

1810647 DMKI-FPTER1

designation	Telis Soliris RTS US Patio			
reference	1810647			
range	RTS New Collection			

FUNCTIONS

One channel hand held transmitter compatible with the RTS receivers but dedicated to the SOLIRIS receiver RTS and the radio built in motors which have wind & sun feature.







STREET COLUMN				
E E -	I TABLET A RESIDEN		PER TRANSPARENT	
TECHN		Po 1 and said 97 [

Box

Material

Color

Protection factor against solid & splashproof

ABS and SEBS Shock resistant Blue & White 145 x 49 x 22 mm

IP 44

Battery

Voltage

Type

3V 2430 Lithium

Battery life time

(at ambient temperature)

3 years (4 actions of 1" per day)

Frequency Radiated power Modulation type Protocole

433.42 Mhz +/- 100 kHz -13 dBm or 0.05 mW

ASK type A1

RTS

Standard

FCC ID: DWN

Temperature range

Range (minimum guaranteed)

Storage

- 20°C / + 70°C 0°C / + 60°C

Antenna

Working

Integrated

50 m in free field

Weight

approx. 70g

R&D Name: Date:

E. SERNET 18/04/2017 SI

QUALITY Name:

Date:

Name: Date:

EDITOR F. BROZILLE 18-04-2007 3