

30 - 03 - 2007

1810651 DMKI-FPTER1

designation	Telis 4 RTS Lounge
reference	1810651
range	RTS New Collection

FUNCTIONS

Four channel hand held transmitter compatible with the RTS receivers range.



TECHNICAL SPECIFICATIONS

Box	Material	ABS & SEBS
	Color	Shock resistant
	Size	Black
	Protection factor against solid & splashproof	145 x 49 x 22 mm
		IP 30
Battery	Voltage	3V
	Type	2430 Lithium
Battery life time (at ambient temperature)		3 years (4 actions of 1" per day)
Frequency		433.42 Mhz +/- 100 kHz
Radiated power		0dBm or 1 mW
Modulation type		ASK type A1
Protocole		RTS
Standard		EN 60730 - 2 - 1 EN 300220 - 3 EN 301489 - 3
Temperature range	Storage	- 20°C / + 70°C
	Working	0°C / + 60°C
Antenna		Integrated
Range (minimum guaranteed)		20 m with 2 reinforced concrete walls
Weight		approx. 70g

R&D

Name:

E. SERNET

Date:

20/04/2007 *E. Sernet*

QUALITY

Name:

X. COLET

Date:

20/04/2007 *X. Colet*

EDITOR

Name:

F. BROZILLE

Date:

20-04-2007 *F. Brozille*