MOTORS
Range 2
120V – 60Hz

REFERENCE	PRODUCT	PACKAGING DIMENSION (cm)
1030055	506S2 ILT2 6/38 VVF 2M UNIT	76 x 9.5 x 10
1103020	515S2 ILT2 15/38 VVF US 2M UNIT	76 x 9.5 x 10
1030075	535A2 ILT2 35/20 VVF 2M UNIT	76 x 9.5 x 10
1100019	506S2 ILT2 6/38 VVF 2M DATA 0,3M	76 x 9.5 x 10
1100026	515S2 ILT2 15/38 VVF 2M DATA 0,3M	76 x 9.5 x 10
1100027	535A2 ILT2 35/20 VVF 2M DATA 0,3M	76 x 9.5 x 10

	1030055	1103020	1030075	1100019	1100026	1100027
Torque (Nm)	6	15	35	6	15	35
Speed (rpm)	38		20	38		20
Max. Current consumption (A)	0.95	1.8	2.1	0.95	1.8	2.1
Power (W)	110	210	250	110	210	250
Motor weight (Kg)	2.07	2.77	2.77	2.07	2.77	2.77
Power Level (dBA)	55	56	58	55	56	58
Voltage	120V (108 to 132V)					
Voltage Frequency	60Hz					
Protection Index	IP44					
Head	Star					
Power cable	Included / 2m / 3 wires					
Data cable	Included / **1.5m** / 4wires / RJ9 phone connectors			Included / **0.3m** / 4wires / RJ9 phone connectors		

MOTORS
Range 2
120V – 60Hz

REFERENCE	PRODUCT	PACKAGING DIMENSION (cm)
1030074 *	506S2 ILT2 6/38 RH VVF 2M UNIT	76 x 9.5 x 10
1103017 *	515S2 ILT2 15/38 RH VVF US 2M	76 x 9.5 x 10
1030076 *	535A2 ILT2 35/20 RH VVF 2M UNIT	76 x 9.5 x 10

** ILT2 RH motors are available only for one customer in USA*
ILT2 RH cannot be ordered by any other country

	1030074 *	1103017 *	1030076 *
Torque (Nm)	6	15	35
Speed (rpm)	38		20
Max. Current consumption (A)	0.95	1.8	2.1
Power (W)	110	210	250
Motor weight (Kg)	2.09	2.77	2.77
Power Level (dBA)	55	56	58
Voltage	120V (108 to 132V)		
Voltage Frequency	60Hz		
Protection Index	IP44		
Head	Round		
Power cable	Included / 2m / 3 wires		
Data cable	Included / 1.5m / 4wires / RJ9 phone connectors		

Quiet M O T O R S
Range 2
120V – 60Hz

REFERENCE	PRODUCT	PACKAGING DIMENSION (cm)
1030094	504S2 SONESSE ILT2 VVF SHORT UNIT	87 x 12.5 x 12.5
1030053	504S2 SONESSE ILT2 VVF 2M UNIT	87 x 12.5 x 12.5
1030081	504S2 SONESSE ILT2 VVF 2M BAR (x 5)	-
1030077 *	504S2 SONESSE ILT2 RH VVF 2M UNIT	87 x 12.5 x 12.5
1030085 *	504S2 SONESSE ILT2 RH VVF 2M BAR (x 5)	-

** ILT2 RH motors are available only for one customer in USA*
ILT2 RH cannot be ordered by any other country

	1030094	**1030053** (1030081)	**1030077 *** (1030085 *)
Torque (Nm)	4		
Speed (rpm)	32		
Max. Current consumption (A)	0.95		
Power (W)	110		
Motor weight (Kg)	2.875		
Power Level (dBA)	≤ 44		
Voltage	120V (108 to 132V)		
Voltage Frequency	60Hz		
Protection Index	IP31		
Head	Star		Round
Power cable	Included / 2m / 3 wires		
Data cable	Included / **0.3m** / 4wires / RJ9 phone connectors	Included / **2.5m** / 4wires / RJ9 phone connectors	