



ILT2 TECHNICAL DATA

TS - FPTE

RANGE 2

ILT2 Range2 R0


25/02/08

Page 1/2

Nominal voltage	120 V - 60 Hz
Power supply tolerances	108 - 132 V
Thermal time	5 minutes
Number of wires of the cable	3
Wire section	AWG 18
Type of limit switch unit	Electronic
Capacity of the LSU	300 turns
Repeatability	< ± 2°
System of protection	IP 44
Interface drawings	206821 : Wheel Interface LT50 206822 : Crown Interface LT50 206810 : Screw Implantation for LT50 mounting 206823 : Star Head LT50, LT50 PA/PS
Basic crown for tube Ø	50 x 1,5 mm
Phone Cable Connector	flat 4-point ; RJ9 type, male plug.
Electromagnetic Compatibility	IEC 1000 - 4 - 2 IEC 1000 - 4 - 3 3V/m IEC 1000 - 4 - 4 level III IEC 1000 - 4 - 5 1kV IEC 1000 - 4 - 6 3V/m IEC 1000 - 4 - 11 EN 55014
Temperature working range	Normal use : -20°C to +70°C
Noise Level	According to SOMFY measurements (for information only). Worse value : in load up direction during 10 seconds.

Designation	Nm / in.lbf	rpm		mm	mm	mm	mm	W	A	°C		kg	dBA		
	Nominal torque	No-load Speed	reference	L1 max.	L2 (±3 mm)	L3 max.	tube	Rated power	Rated current	Thermal tripping	Brake type	Weight	Noise		
506S2 ILT2 6/38	6 / 53	38	200839B	605	590	613	540	110	0,95	140	sliding	2.07	55		
515S2 ILT2 15/38	15 / 132	38	200841A	675	660	683	610	210	1,8	140	sliding	2.77	56		
535A2 ILT2 35/20	35 / 310	20	200837A	675	660	683	610	250	2,1	140	sliding	2.77	58		

WIRING	Neutral	White
	Live	Black
	Earth	Green



R & D		QUALITY		AUTHOR	
Name <i>Aurèle MULET</i>		Name <i>Xavier COLET</i>		Name <i>Franck BROZILLE</i>	
Date <i>25/02/2008</i>	Visa <i>[Signature]</i>	Date <i>25/02/2008</i>	Visa <i>[Signature]</i>	Date <i>25-02-2008</i>	Visa <i>[Signature]</i>